

Performance criteria

Tested according to	EN 1906
with 9 mm square spindle fire protection tested according to DIN 18273	F
Lever handle shape suitable for emergency exits and fire barrier doors	EN 179
Return spring with 90° stop	■
Fixed sleeve nuts / supporting cams	■
Fixed swivel-mounted lever handle	■
Grooved ball bearing with flexible/compensating bearing	■
Steel substructure with nylon clip ring	■
Concealed, continuous screw attachment	■
DIN L / R	■
EN 1906 – corrosion class 5	■
1 million test cycles (MPAZert)	■

Classification key EN 1906

4	D9	-	B1	1	5	0	B/U
---	----	---	----	---	---	---	-----

■ Yes – No □ Optional




Steel door



Wooden door

PRODUCT FAMILY D-300

Standard fitting



D-310



D-330



D-330 .

Handle on short plate

Handle on oval rose



D-310 .



D-315



D-335 .

Security handle



D-310



D-315


Window handle



FO-310 .

Material:

ER ER
Stainless steel




Material:

ER ER Stainless steel **AI** AI Aluminium

Bearing technology:




D-330 round rose



D-330 round rose with OKL Magis – ball-bearing technology

Object fitting with a maintenance-free closed ball bearing and integrated flexible bearing for lever handle guidance. Fixed substructure with spring reset and a 90° fixed stop. Steel substructure with positioning studs and integrated fixing bolts. Concealed, continuous screw attachment, cover roses in an angular design. For knob/lever fittings, please note the DIN direction. User category class 4, corrosion class 5, supporting cams $\varnothing 8 \times 5$ mm



OKL MAGIS – HANDLE ON ROUND ROSE




				Fittings set							
S	21 mm	8 mm		PZ	RZ	BB	WC-SK	K-135	K-165	K-160	K-116
Can be used for DIN L/R				173305.46 97	173325.46 97	173300.46 97	173320.46 97	On request	On request	On request	On request
	(1) DIN R knob hinge side							173311.46 97	173331.46 97	173341.46 97	173381.46 97
	(2) DIN L knob Opposite hinge side							173311.46 97	173331.46 97	173341.46 97	173381.46 97
	(3) DIN L knob hinge side							173310.46 97	173330.46 97	173340.46 97	173380.46 97
	(4) DIN R knob Opposite hinge side							173310.46 97	173330.46 97	173340.46 97	173380.46 97


F	21 mm	9 mm		PZ	RZ	BB	WC-SK	K-135	K-165	K-160	K-116
Can be used for DIN L/R				373305.46 74	373325.46 74	On request	On request	On request	On request	On request	On request
	(1) DIN R knob hinge side							373311.46 74	373331.46 74	373341.46 74	373381.46 74
	(2) DIN L knob Opposite hinge side							373311.46 74	373331.46 74	373341.46 74	373381.46 74
	(3) DIN L knob hinge side							373310.46 74	373330.46 74	373340.46 74	373380.46 74
	(4) DIN R knob Opposite hinge side							373310.46 74	373330.46 74	373340.46 74	373380.46 74

Finish: matt brushed. PVD and polished on request
Panic model with passive leaf (with supporting cams), passive leaf (without supporting cams) and UG models available on request.


Lever handle facing left



Lever handle facing right



D-330 round rose




D-330 round rose with OGL Click – friction bearing technology

Maintenance-free lever handle guidance integrated into a steel/nylon base rose as a friction bearing. Spring assistance. Fixed swivel-mounted lever handle with ECO Click system for quick and easy installation. Steel substructure with positioning studs and integrated fixing bolts. Can be used for DIN left/DIN right. Concealed, continuous M5 screw attachment.

User category class 4. Supporting cams $\varnothing 8 \times 5$ mm. Available with and without supporting cams



OGL CLICK – HANDLE ON ROUND ROSE




EN 1906 EN 179 F

F = 4 7 - B1 1 4 0 A

OGL Click			Fittings set						Passive leaf fittings set		
	\varnothing	\sphericalangle									
S	21 mm	8 mm		5030049290	5030049296	5030049291	5030049292	5030049294	5030049295		
F	21 mm	9 mm		5030049299	5030049297		5030049303		5030049307	5030049308	5030049310
	21 mm	9 mm									

Finish: matt brushed. PVD and polished on request



EN 1906 EN 179 F

F = 4 7 - D1 1 4 0 A

OGL Click			Fittings set						Passive leaf fittings set		
	\varnothing	\sphericalangle									
S	22 mm	8 mm		5030049479	5030049485	5030049480	5030049481	5030049483	5030049484		
F	22 mm	9 mm		5030049488	5030049486		5030049490		5030049492	5030049494	5030049495
	22 mm	9 mm									

Finish: F1 anodised aluminium; further colours available on request.


D-330 round rose



D-330 round rose with OGL – friction bearing technology

Lever handle guidance with a maintenance-free friction bearing made of self-lubricating nylon. Fixed swivel-mounted lever handle. Can be used for DIN left/DIN right. Steel substructure with positioning studs. Non-visible, continuous screw attachment.

User category class 4, supporting cams $\varnothing 8 \times 5$ mm



OGL – HANDLE ON ROUND ROSE




EN 1906 EN 179

= 4 7 - B1 1 4 0 U



	Ø	▧	Fittings set						Passive leaf fittings set	
	21 mm	8 mm		156805.46	156800.46	156810.46	156880.46	156820.46		
	21 mm	9 mm	316851.46	356801.46		356860.46	356882.46		356818.46	356817.46
	21 mm	9 mm		356850.46						

Finish: matt brushed. PVD and polished on request



EN 1906 EN 179


= 4 7 - D1 1 4 0 U



	Ø	▧	Fittings set						Passive leaf fittings set	
	22 mm	8 mm		157205.30	157200.30	157210.30	157220.30			
	22 mm	9 mm	317029.30	357800.30		357860.30		357804.30	357818.30	357817.30
	22 mm	9 mm		357850.30						

Finish: F1 anodised aluminium; further colours available on request.


D-330 round rose SGL Click



D-330 round rose with SGL – friction bearing technology

Maintenance-free lever handle guidance integrated into the nylon base rose as a friction bearing. With spring assistance. Fixed swivel-mounted lever handles with ECO **CLICK** system for quick installation. Nylon substructure with supporting cams. Can be used for DIN left / DIN right. Concealed, continuous M5 screw attachment.

User category class 3, supporting cams Ø 8 x 7 mm



SGL – HANDLE ON ROUND ROSE



S = 3 7 - 0 1 4 0 A

		Fittings set				
S	21 mm	8 mm	5030060750	5030060748	5030060803	5030060752

Finish: matt brushed. PVD and polished on request

Product information and use of ECO fitting technology

§ 1 Product information and intended usage

1. The fitting systems made by ECO are assistive systems that can be used to help with opening and closing motions and/or locking processes for doors, glass doors and window elements.
2. The fixing elements supplied with these products must be used and installed according to the mounting instructions/specifications.

§ 2 Improper use of the products

Improper use of fitting systems for doors and windows (i.e. not using the product as intended) includes the following situations in particular:

- Installation or mounting of foreign objects and/or objects not intended for this purpose into the fitting system;
- Using auxiliary tools to operate the system;
- The fittings are used as a replacement for a missing wall buffer;
- Fittings are misused as a suspension device for heavy loads;
- Fittings are used long-term in combination with panic locks instead of only in emergencies, against the recommendation of the lock and fitting industry;
- Surface of the fitting systems damaged by the use of sharp or hard objects;
- The use of fasteners made by third-party manufacturers.

Sooner or later, these errors will cause damage, and the products will no longer have the characteristics defined by the manufacturer.

§ 3 Product performance

1. Product performance is only partially governed by standards. Many aspects of product performance have been developed based on years of experience and should be considered common knowledge in the construction hardware industry. Correspondingly, the contents of these standards and these empirical values should also be applied to fittings that are not expressly regulated.
2. Specifically, the following standards apply:
 - EN 1906: General benchmarks for door fittings and accessories;
 - DIN 18273: Special rules for fire and smoke control doors;
 - DIN 18257: Minimum security requirements for security fittings.
3. The fitting system must be replaced if, despite maintenance and servicing, it can no longer be ensured that it will function properly, and/or it may pose a risk of injury.
4. Furthermore, the products are continuously being improved, and manufacturing is subject to quality assurance. The right to make technical changes is reserved.

§ 4 Product maintenance

1. The user must ensure that the fitting systems and fixing elements are installed in a proper functional manner.
2. Depending on the material and where they are used, the products will face a certain degree of natural wear and tear. Consequently, all moving parts must undergo maintenance at least once per year; i.e. the proper fit, stability of the screw connections etc. must be checked on a regular basis. Only water, gentle cleaning agents and other cleaning agents that do not contain corrosive ingredients should be used for cleaning the fitting systems.
3. Manufacturing primarily uses the materials nylon, aluminium, stainless steel and brass. Please note that each of these different materials has different maintenance and servicing requirements.

§ 5 Duty to inform and instruct

1. The following documents are available to provide information and instruction:
 - Catalogues and brochures;
 - Tender documents;
 - Procurement information;
 - Bid documents;
 - Installation and operating instructions;
 - DIN standards.
2. In order to ensure that the fitting systems function properly:
 - Architects, planners and any other people involved in the process are required to request all the necessary product information from us and to comply with said information,
 - Specialised retailers are required to observe the product information and notes in the price lists and catalogues and, in particular, to request all required instructions from us and to pass them on to the processors,
 - The processors are required to obtain all product information and to comply with it, and, in particular, to request the operating and maintenance instructions from us and pass them on to the customers and users.

Overall, all parties involved must ensure that the fitting systems are properly assembled and installed and that each end user receives proper instructions and explanations.

General information

ECO Schulte recommends

For lever handle sets without a return spring, we recommend using locks that comply with DIN 18251 - class 3 or higher

In order to minimise the clearance between the lever handle set and the lock, we recommend locks that comply with DIN 18251 with a clamping nut.

When ECO handles are properly installed and used, the paint should withstand daily use. Excessive contact with hard or sharp objects (such as key rings, rings etc.) can scratch the surface. This does not impair functionality, however.

Our Compendium presents a compilation of all the products in our range. These are each subject to different supply classes. Special models are often configured to specific customer wishes and sometimes require longer lead-times and minimum order quantities. Your contact will be happy to advise you.

ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89

D-58706 Menden

Telephone +49 2373 9276 - 0

Telefax +49 2373 9276 - 40

info@eco-schulte.de

www.eco-schulte.de

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured to customer specifications and sometimes require longer delivery times and minimum purchase quantities. Further advise can be given by your contact person.

■ SYSTEM TECHNOLOGY FOR THE DOOR

