








Performance criteria		
Closer types	PZ-72	■
	RZ-74	□
Backset	65	■
	80	■
Panic function	B	■
	C	■
	D	■
	E	■
Forend	Stainless steel	■
Forend width	20 round (rebate)	■
	24 rectangular (flush)	■
Nut	9 mm	■
Suitable for fire and smoke control doors	F	■
Tested and approved according to DIN/EN standards	EN 179 	■
	EN 1125 	
	EN 12 209	
<p>■ Yes - No □ On request</p>		
<p> Wooden door  Steel door</p>		



Dimensions: GBS 140

Description

- Mortise lock for fire doors with device for additional latch bolt for top locking
 - Tested and approved according to **EN 12 209**
 - Panic option: Tested and approved according to **EN 179** and **EN 1125**
 - For double-leaf wooden and steel doors and fire doors
 - Essential accessories: Locking bar with spring and snap lock
 - Rectangular forend available on request
 - For accompanying GBS 94 passive leaf lock, see our main catalogue
 - Compatible accessories
- Individual stamping available on request at additional cost.w

**GBS 14x ■ Mortise lock for double-leaf fire doors ■ Set-up for additional latch bolt for top locking****GBS 141 panic function E**

Forend Surface	Backset in mm	Forend Shape	Forend 20 x 285 mm / PZ-72 with knob/lever		Forend 24 x 285 mm / PZ-72 with knob/lever	
			DIN L	DIN R	DIN L	DIN R
ER	65	Round	20141ja02H34300	20141ja02H34400	20141ja02M34300	20141ja02M34400
	80	Round	20141ma02H34300	20141ma02H34400	20141ma02M34300	20141ma02M34400

GBS 142 panic function D

Forend Surface	Backset in mm	Forend Shape	Forend 20 x 285 mm / PZ-72		Forend 24 x 285 mm / PZ-72	
			DIN L	DIN R	DIN L	DIN R
ER	65	Round	20142ja02H35100	20142ja02H35200	20142ja02M35100	20142ja02M35200
	80	Round	20142ma02H35100	20142ma02H35200	20142ma02M35100	20142ma02M35200

GBS 143 panic function B

Forend Surface	Backset in mm	Forend Shape	Forend 20 x 285 mm / PZ-72		Forend 24 x 285 mm / PZ-72	
			DIN L	DIN R	DIN L	DIN R
ER	65	Round	20143ja02H33100	20143ja02H33200	20143ja02M33100	20143ja02M33200
	80	Round	20143ma02H33100	20143ma02H33200	20143ma02M33100	20143ma02M33200

GBS 144 panic function C

Forend Surface	Backset in mm	Forend Shape	Forend 20 x 285 mm / PZ-72		Forend 24 x 285 mm / PZ-72	
			DIN L	DIN R	DIN L	DIN R
ER	65	Round	20144ja02H32100	20144ja02H32200	20144ja02M32100	20144ja02M32200
	80	Round	20144ma02H32100	20144ma02H32200	20144ma02M32100	20144ma02M32200

Product information and usage of ECO lock technology

§ 1 Product information and intended usage

1. The locks produced by ECO are intended for closing and locking doors.
2. To ensure that the locks will function properly for their intended usage, the correct combination of approved fittings, closure mechanisms and accessories is absolutely necessary. The locks must be installed in accordance with the installation instructions and taking into account the applicable DIN standards, including maintenance; locks for doors with special functions must be selected according to requirements and also labelled as necessary.

§ 2 Improper use of the products

Improper use of locks (i.e. not using the product as intended) includes the following situations in particular:

- Using the extended bolt to keep the door open in contravention of the intended use;
- Adjusting the hinges or lowering the door, if this results in the required clearance between the door and the frame becoming larger or smaller;
- Installation impedes functionality or the closing elements are retroactively treated;
- Installation or mounting of foreign objects and/or objects intended for this purpose into the lock or the strike plate;
- The handle connection is subjected to loads heavier than standard hand force;
- Opening a double-leaf door via the passive leaf, if this is not an approved use;
- Using closure mechanisms that are not included with the product (that deviate significantly or are improperly calibrated);
- Intervening in or affecting the lock or strike plate in any way that results in a change in its structure, operation or function;
- Simultaneously operating the lever handle and the locking mechanism;
- Closing the door when gripping between the door leaf and the frame.

Sooner or later, these errors will cause damage, and the products will no longer have the characteristics defined by the manufacturer.

§ 3 Product performance

1. Product performance is only partially governed by standards. Many aspects of product performance have been developed based on years of experience and should be considered common knowledge in the construction hardware industry. Correspondingly, the contents of the standards and these empirical values should also be applied to locks that are not expressly regulated.
2. In particular, the standards **DIN 18250, DIN 18251, DIN 18252, DIN 18254, DIN 18255, DIN 18257 and DIN 18273** apply, as does the current standard on fittings, which defines the basic requirements and additional requirements for locks.

3. Locks must be replaced if, despite maintenance and servicing, it can no longer be ensured that they will function properly, and/or they may pose a risk of injury.
4. Furthermore, the products are continuously being improved, and manufacturing is subject to quality assurance. The right to make technical changes is reserved.

§ 4 Product maintenance

1. The user must ensure that the locks function properly.
2. Depending on the material and where they are used, the products will face a certain degree of natural wear and tear. Consequently, depending on the level of use, the locks must undergo maintenance at least once per year; i.e. an appropriate lubricant must be applied at regular intervals. Only cleaning agents that do not contain corrosive ingredients should be used for cleaning the locks.
3. A range of different materials are used in manufacturing. Please note that each of these different materials has different maintenance and servicing requirements.

§ 5 Duty to inform and instruct

1. The following documents are available to provide information and instruction:
 - Catalogues and brochures;
 - Bid documents;
 - Tender documents;
 - Installation and operating instructions;
 - Procurement information;
 - DIN standards.
2. In order to ensure that the locks function properly:
 - Architects, planners and any other people involved in the process are required to request all the necessary product information from us and to comply with said information,
 - Specialised retailers are required to observe the product information and notes in the price lists and catalogues and, in particular, to request all required instructions from us and to pass them on to the processors,
 - The processors are required to obtain all product information and to comply with it, and, in particular, to request the operating and maintenance instructions from us and pass them on to the customers and users.

Overall, all parties involved must ensure that the locks are properly assembled and installed and that each end user receives proper instructions and explanations.

General information

ECO Schulte recommends

For lever handle sets without a return spring, we recommend using locks that comply with DIN 18251 - class 3 or higher

In order to minimise the clearance between the lever handle set and the lock, we recommend locks that comply with DIN 18251 with a clamping nut.

When ECO handles are properly installed and used, the paint should withstand daily use. Excessive contact with hard or sharp objects (such as key rings, rings etc.) can scratch the surface. This does not impair functionality, however.

Our Compendium presents a compilation of all the products in our range. These are each subject to different supply classes. Special models are often configured to specific customer wishes and sometimes require longer lead-times and minimum order quantities. Your contact will be happy to advise you.

ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89

D-58706 Menden

Telephone +49 2373 9276 - 0

Telefax +49 2373 9276 - 40

info@eco-schulte.de

www.eco-schulte.de

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured to customer specifications and sometimes require longer delivery times and minimum purchase quantities. Further advise can be given by your contact person.

■ SYSTEM TECHNOLOGY FOR THE DOOR

