

# Bedix

## Door leaf and secondary closing edge monitoring with laser sensors



---

### Bedix

- External operation and programming console for wall mounting in-wall or on-wall
- With illuminated two-line display and 4 control buttons
- Functions (password-protected)
- All parameters and configurations can be adjusted
- Diagnostics menu and error analysis
- Remote reset/teaching
- Different program types can be set: Automatic, KEY, always open, manual, one-way
- Voltage supply: 12-24 V
- Protection rating: IP20
- Dimensions: Height 85 mm, width 85 mm

---

<b>BEDIX (UP)</b>	5030024838	Operation and programming console (in-wall installation)
<b>AP-BEDIX</b>	5030026428	On-wall installation frame for D-BEDIX
<b>Combi BEDIX PZ-AP</b>	5030037345	Combination device comprising Bedix and a key switch for unlocking (unauthorised use) <ul style="list-style-type: none"><li>▪ Set up for on-site PZ</li><li>▪ Incl. double on-wall frame</li></ul>
<b>Combi BEDIX PZ-UP</b>	5030035366	Combination device comprising Bedix and a key switch for unlocking (unauthorised use) <ul style="list-style-type: none"><li>▪ Set up for on-site PZ</li><li>▪ For in-wall installation</li></ul>

---

**ECO Schulte GmbH & Co. KG**

Iserlohner Landstraße 89

D-58706 Menden

Telephone +49 2373 9276 - 0

Telefax +49 2373 9276 - 40

[info@eco-schulte.de](mailto:info@eco-schulte.de)

[www.eco-schulte.de](http://www.eco-schulte.de)

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured to customer specifications and sometimes require longer delivery times and minimum purchase quantities. Further advise can be given by your contact person.

## ■ SYSTEM TECHNOLOGY FOR THE DOOR

